
## SUBMITTAL DATA SHEET

Jet Pumps Convertible | Shallow Well

## **Square Flange Motor**





## Two Compartments Products | E-Z Access

Part				Catalog		Service	SF*	MTR	Ship	Factory
No.	HP	RPM	Frame	Volt	Туре	Factor	AMPS	LGTH(1)	Wt.	Wired
6164-203	1/3	3500	48Y	115/230	FNP	1.95	10.6/5.3	11.23"	17	115V
6164-200	1/2	3500	48Y	115/230	FHP	1.90	11.2/5.6	12.0"	19	115V
6164-201	3/4	3500	48Y	230/115	FHP	1.65	7.6/14.3	12.27"	22	230V
6164-202	1	3500	48Y	230/115	FHP	1.65	9.2/18.4	12.35"	24	230V

<sup>\*</sup>Service Factor Amps. may vary with motor manufacturer - refer to label on motor

## Features:

- 303 Stainless steel shaft
- Shaft threads 7/16-20 UNF-2A, 0.625" Diameter, .91" long from face
- Ball bearings (locked drive end bearing)
- Continuous duty at 40°C/104°F Amient, 60Hz
- Automatic reset thermal overload protector
- Round frame (without base)
- Power leads and ground wire supplied for proper connection to the pressure switch
- Voltage change device

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



A.Y. McDonald Mfg. Co. P.O. Box 508

Dubuque, IA 52004-0508

Toll Free: 1-800-292-2737 Fax: 1-800-832-9296

Hours: 7:00 a.m. - 5:00 p.m., CST

sales@aymcdonald.com www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

<sup>(1)</sup> Length not including shaft