

NES Series Water Softeners







...THE NEXT GENERATION

LOADED WITH FEATURES



EASY TO PROGRAM

JUST PUSH THE BUTTON TO SET THE TIME OF DAY AND HARDNESS...

YOU'RE DONE!

CONTROL VALVE DESIGNED FOR MINIMUM WATER AND SALT USAGE.



BRINE VALVE

ELIMINATES MESSY OVERFLOW SHOULD A MALFUNCTION OCCUR

SALT SHELF

ALLOWS THE USE OF INEXPENSIVE SALT AND REDUCES THE CHANCE OF SALT BRIDGING AND MUSHING

OPTIONAL ADVANCED PROGRAMMING

ADJUSTMENT OF EACH CYCLE **DURATION**; REGENERATION TIME; AND DAYS OVER-RIDE

RUGGED RESIN TANK

FIBERGLASS CONSTRUCTION, WILL NEVER RUST OR CORRODE

VORTEX DISTRIBUTOR

SCRUBS THE RESIN EACH REGENERATION TO EXTEND THE LIFE OF THE SOFTENER

SELF LEVELING BASE

COMPENSATES FOR UNLEVEL FLOOR

EASY TO INSTALL... EASY TO SERVICE



QUICK RELEASE DRAIN FITTING

NO THREADS TO LEAK.
MERELY PULL CLIP TO
REMOVE DRAIN FITTING





PUSH-IN BRINE LINE FITTING

ELIMINATES CONFUSING FERRULES AND NUTS THAT CAN CAUSE LEAKS



STAINLESS STEEL BYPASS

OPERATES WITH SINGLE HANDLE. 3/4" FEMALE THREADS

NES SERIES

SPECIFICATIONS

Model Number	Grain Capacity		Service Flow Rate (gpm)		Salt Storage	Dimensions *Inlet Height				Pipe
	Max.	Min.	Peak	Service	(lbs.)	Α	*B	С	D	Size
NES-0.75-S	22,500	21,000	12	6	200	52"	45.75"	23"	15"	3/4"
NES-1-S	30,000	24,000	13	8	200	56"	49.75"	24"	15"	
NES-1.5-S	45,000	33,000	13	10	200	62"	56"	25"	15"	or 1"
NES-2-S	60,000	48,000	14	12	200	56"	49.75"	27"	15"	(-1S suffix)
NES-2.5-S	75,000	48,500	15	14	200	62"	56"	32"	18"	

SPACE-MAKER

Model Number	Grain Capacity		Service Flow Rate (gpm)		Salt Storage	Dimensions *Inlet Height				Pipe Size
	Max.	Min.	Peak	Service	(lbs.)	Α	*B	С	D	0.20
NECS-0.75-S	22,500	21,000	14	6	150	43"	36.50"	23"	13"	3/4"
NECS-1-S	30,000	24,000	14	8	150	43"	36.50"	23"	13"	3/4"

NOTE: Service flow rate of control valve (only) is 20gpm @ 15 psig drop.



